



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
23.05.2001 Bulletin 2001/21

(51) Int Cl.7: **B60G 21/055, B60G 15/07**

(21) Application number: **00124741.0**

(22) Date of filing: **13.11.2000**

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
Designated Extension States:
AL LT LV MK RO SI

(71) Applicant: **KIA MOTORS CORPORATION**
Youngdeungpo-gu, Seoul (KR)

(72) Inventor: **Cho, Seong Un**
Incheon 405-762 (KR)

(30) Priority: **16.11.1999 KR 9950842**


(74) Representative: **Vlering, Jentschura & Partner**
Postfach 22 14 43
80504 München (DE)

(54) **Stabilizing arrangement for vehicle suspensions**

(57) A stabilizer in which a shock absorber bracket (20) is fixedly engaged with the upper end of the control link (30) at the center of the shock absorber (10) on which the coil spring (50) is installed. A stabilizer (40) is engaged with the lower end of the control link (30) of which upper end is engaged with the shock absorber bracket (20). In case that the wheels in opposite on the drum of the vehicle are simultaneously actuated, the stabilizer (40) twists to make momentum of the wheels

in opposite the same, to prevent the body from being inclined. When the right and left wheels receive the impact or rebound during cornering, the stabilizer (40), shock absorber (10) and the coil spring (50) are simultaneously actuated to maintain roll stiffness to keep the balance of the vehicle, so that passenger's comfort is improved. The stabilizer (40) may absorb and disperse impact load applied to the tire from the road condition, thereby improving the steering capability.

FIG. 3



Description.

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0001] The present invention relates to a stabilizer of the vehicle and more particularly to a stabilizer structure for maintaining roll stiffness to keep the balance by actuating the shock absorber, coil spring and stabilizer despite impact or rebound applied to right and left wheels.

2. Description of the Related Art

[0002] Generally, the vehicles include a coil spring for buffering vibrations from the road condition, shock absorber for improving driver's comfort by controlling free vibrations of the coil spring, and the stabilizer for preventing rolling of the car.

[0003] Conventional stabilizer structure is shown in Figs. 1 and 2, in which the lower end of the control link 30' is engaged by nut with one part of lower arm 20' on which one end of the shock absorber 10' is installed. On the upper part of the control link 30' engaged with the nut 31' one end of the stabilizer 40' is engaged with the nut 31'.

[0004] One end of the stabilizer 40' is engaged by nut 31' on the upper end of the control link 30' of which lower end is engaged with the end of lower arm 20', so that the wheels in opposite are driven. The stabilizer 40' twists to make the wheels to simultaneously drive, thereby serving to prevent the vehicle body from being inclined.

[0005] However, this type of stabilizer 40' allows installation only by nut engagement on the upper end of the control link 30' of which lower end is nut engaged on the lower arm 20'. This installation structure has a disadvantage that the stabilizer 40' is not actuated at the time of impact or rebound applied to the wheels in opposite.

Accordingly, it is necessary to establish high constant of the coil spring 50' in order to maintain roll stiffness by the shock absorber 10' and the coil spring 50' disposed around the shock absorber 10'.

[0006] However, maintaining roll stiffness during cornering by the shock absorber 10' and the coil spring 50 to increase constant value of the coil spring 50' makes elasticity of the coil spring 50' low, thereby resulting in passengers' discomfort.

SUMMARY OF THE INVENTION

[0007] Accordingly, it is an object of the present invention to solve the above disadvantages of the conventional stabilizer.

[0008] In order to achieve the object of the present invention, there is provided a stabilizer structure including a shock absorber bracket engaged with the upper

end of the control link 30 at the center of the shock absorber 10 on which the coil spring 50 is installed. A stabilizer 40 is engaged with the lower end of the control link 30 of which upper end is engaged with the shock absorber bracket 20. In case that the wheels in opposite on the drum of the vehicle are simultaneously actuated, the stabilizer 40 twists to make the wheels to simultaneously drive, so as to prevent the body from being inclined. When the right and left wheels receive the impact or rebound during cornering, the stabilizer 40, shock absorber 10 and the coil spring 50 are simultaneously actuated to keep roll stiffness, thereby improving the passenger's comfort. The stabilizer 40 may absorb and disperse impact load applied to the tire from the road condition, thereby improving the steering capability.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] The present invention will become more fully understood from the detailed description given hereinbelow and the accompanying drawings which are given by way of illustration only, and thus, are not limitative of the present invention, and wherein:

Fig. 1 is a perspective view of the conventional stabilizer structure;

Fig. 2 is a front view of the stabilizer structure of Fig. 1; and

Fig. 3 is an exploded perspective view of the stabilizer according to the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0010] As shown in Fig. 2, it is shown the stabilizer structure including a shock absorber bracket fixedly engaged with the upper end of the control link 30 at the center of the shock absorber 10 on which the coil spring 50 is installed. A stabilizer 40 is engaged with the lower end of the control link 30 of which upper end is engaged with the shock absorber bracket 20.

[0011] In case that the wheels in opposite on the drum of the vehicle are simultaneously actuated, the stabilizer 40 twists to make momentum of the wheels in opposite the same, to prevent the body from being inclined. When the right and left wheels receive the impact or rebound during cornering, the stabilizer 40, shock absorber 10 and the coil spring 50 are simultaneously actuated to maintain roll stiffness to keep the balance of the vehicle.

The stabilizer 40 functions to absorb and disperse impact load applied to the tire from the road condition, thereby improving the steering capability.

[0012] When the vehicle receives the exterior impact, the stabilizer 40, shock absorber 10 and the coil spring 50 function to maintain roll stiffness to keep the balance of the vehicle, so that the passenger's comfort is improved. The stabilizer 40 of the present invention functions to absorb and disperse the impact load applied to

the tire from the road condition, so that the steering capability is improved.

Claims

1. Stabilizer for use in an vehicle, characterized in that a shock absorber bracket fixedly engaged with the upper end of the control link (30) at the center of the shock absorber (10) on which the coil spring (50) is installed, the stabilizer (40) engaged with the lower end of the control link (30) of which upper part is engaged with the shock absorber bracket (20).

5

10

15

20

25

30

35

40

45

50

55

FIG. 1
PRIOR ART




FIG. 2
PRIOR ART





FIG. 3





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 00 12 4741

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 4 632 423 A (TANAHASHI HARUHIKO) 30 December 1986 (1986-12-30) * figures 1-5 *	1	B60G21/055 B60G15/07
X	US 5 326 084 A (MEVISSEN PETER ET AL) 5 July 1994 (1994-07-05) * figures 1-4 *	1	
X	US 5 797 618 A (BROKHOLC MICHAL) 25 August 1998 (1998-08-25) * figures *	1	
X	DE 196 33 819 A (OPEL ADAM AG) 26 February 1998 (1998-02-26) * figures *	1	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			B60G
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 1 February 2001	Examiner Tsitsilonis, L
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03 92 (P/C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 00 12 4741

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

01-02-2001

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4632423 A	30-12-1986	JP 6053454 B	20-07-1994
		JP 61200015 A	04-09-1986
		DE 3529642 A	04-09-1986
US 5326084 A	05-07-1994	DE 4201837 C	25-02-1993
		DE 59201236 D	02-03-1995
		EP 0552438 A	28-07-1993
		ES 2067286 T	16-03-1995
		JP 5246225 A	24-09-1993
US 5797618 A	25-08-1998	SE 502905 C	19-02-1996
		AU 2813695 A	25-01-1996
		SE 9402290 A	29-12-1995
		WO 9600663 A	11-01-1996
DE 19633819 A	26-02-1998	NONE	

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82